

## LED Light Inserts – Model 93

0347941

 ADR  
APPROVEDProduct Information 

<b>Description</b>	Model 93 - 12/24V LED Turn & DRL
<b>Height</b>	125.00 mm / 4.92 in
<b>Width</b>	90.00 mm / 3.54 in
<b>Depth</b>	95.00 mm / 3.74 in
<b>Shape</b>	Round
<b>Outer Lens Material</b>	Polycarbonate
<b>Outer Lens Color</b>	Clear
<b>Housing Material</b>	Die-Cast Aluminum
<b>Housing Color</b>	Black
<b>Minimum Operating Temperature</b>	-40 °C
<b>Maximum Operating Temperature</b>	65 °C
<b>Connector or Wiring</b>	Deutsch DT04-4P
<b>Mating Connector</b>	Deutsch DT06-4S
<b>Product Weight</b>	1.00 lbs / 0.45 kgs
<b>Shipping Weight</b>	1.20 lbs / 0.54 kgs

Electrical Specifications 

<b>Input Voltage</b>	12-24V DC
<b>Operating Voltage</b>	10-30V DC
<b>Black Wire</b>	Ground
<b>Yellow Wire</b>	Front Turn
<b>Red Wire</b>	DRL
<b>White Wire</b>	Front Position
<b>Current Draw</b>	1.18A @ 12V DC (Front Turn) 0.45A @ 24V DC (Front Turn) 0.60A @ 12V DC (DRL) 0.35A @ 24V DC (DRL) 0.06A @ 12V DC (Front Position) 0.04A @ 24V DC (Front Position)

## Photometric Specifications

**Nominal LED Color Temperature** 5000 K

**Beam Pattern(s)**  
Forward Lighting - Daytime Running  
Light  
Signalization - Front Position  
Signalization - Turn (Front)

## Additional Specifications

**IP Rating** IP69K

**Warranty**  
Please refer to the Warranty Statement which is available for download on the website

**Certification** ECE Reg 6, 7 & 87

**Pack Quantity** 1