



LED Light Inserts - Model 93

0347941



Description Model 93 - 12/24V LED Turn & DRL

 Height
 125.00 mm / 4.92 in

 Width
 90.00 mm / 3.54 in

 Depth
 95.00 mm / 3.74 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Die-Cast Aluminum

Housing ColorBlackMinimum Operating Temperature-40 °CMaximum Operating Temperature65 °C

Connector or WiringDeutsch DT04-4PMating ConnectorDeutsch DT06-4SProduct Weight1.00 lbs / 0.45 kgsShipping Weight1.20 lbs / 0.54 kgs



Electrical Specifications

Input Voltage12-24V DCOperating Voltage10-30V DCBlack WireGroundYellow WireFront TurnRed WireDRL

White Wire Front Position

Current Draw 1.18A @ 12V DC (Front Turn)

0.45A @ 24V DC (Front Turn) 0.60A @ 12V DC (DRL) 0.35A @ 24V DC (DRL)

0.06A @ 12V DC (Front Position) 0.04A @ 24V DC (Front Position)









Photometric Specifications

~

Nominal LED Color Temperature

Beam Pattern(s) Forward Lighting - Daytime Running

_ight

5000 K

Signalization - Front Position Signalization - Turn (Front)

Additional Specifications

v

IP Rating IP69K

Warranty Please refer to the Warranty

Statement which is available for

download on the website

Certification ECE Reg 6, 7 & 87

Pack Quantity 1



