

# LED Headlights – Model 8700 EVO 2 PRO 'Dual Burn'

## 0557111



### Product Information

<b>Description</b>	Model 8700 EVO 2 PRO - 12/24V LED Headlight Insert - Chrome (SAR Connector)
<b>Height</b>	176.53 mm / 6.95 in
<b>Width</b>	176.53 mm / 6.95 in
<b>Depth</b>	99.82 mm / 3.93 in
<b>Shape</b>	Round
<b>Outer Lens Material</b>	Polycarbonate
<b>Outer Lens Color</b>	Clear
<b>Bezel Color</b>	Chrome
<b>Retrofits</b>	2D1 "PAR56" or 7" Round Headlights
<b>Minimum Operating Temperature</b>	-40 °C
<b>Maximum Operating Temperature</b>	65 °C
<b>Connector or Wiring</b>	Headlight: AMP 282105-1, DRL/FP: AMP 282087-1
<b>Mating Connector</b>	Headlight: AMP 282087-1, DRL/FP: AMP 282105-1
<b>Product Weight</b>	2.31 lbs / 1.05 kgs
<b>Shipping Weight</b>	3.35 lbs / 1.52 kgs



## Electrical Specifications



<b>Input Voltage</b>	12-24V DC
<b>Operating Voltage</b>	9-32V DC
<b>White Wire</b>	Ground
<b>Yellow Wire</b>	Low Beam
<b>Green Wire</b>	High Beam
<b>Brown Wire</b>	Front Position
<b>Orange/White Wire</b>	DRL
<b>Current Draw</b>	3.60A @ 12V DC (High Beam) 2.00A @ 12V DC (Low Beam) 1.80A @ 24V DC (High Beam) 1.10A @ 24V DC (Low Beam) 1.60A @ 12V DC (DRL) 0.80A @ 24V DC (DRL) 0.16A @ 12V DC (Front Position) 0.10A @ 24V DC (Front Position)

## Photometric Specifications



<b>Raw Lumen Output</b>	4170 (High Beam); 2340 (Low Beam)
<b>Effective Lumen Output</b>	1340 (High Beam); 694 (Low Beam)
<b>Candela Output</b>	84700 (High Beam)
<b>Nominal LED Color Temperature</b>	5000 K
<b>Beam Pattern(s)</b>	Forward Lighting - Daytime Running Light Forward Lighting - High Beam (ECE) Forward Lighting - Low Beam (ECE Left Hand) Signalization - Front Position

## Additional Specifications



<b>IP Rating</b>	IP67
<b>Warranty</b>	Please refer to the Warranty Statement which is available for download on the website
<b>Certification</b>	ECE Reg 7, 10, 87 & 112
<b>Pack Quantity</b>	1