LED Safety Light – Model 560 Warning Projector Light

1300661

Product Information

Description	Model 560 - 12/72V Warning Projector Light - RED
Height	118.92 mm / 4.68 in
Width	153.90 mm / 6.06 in
Depth	136.65 mm / 5.38 in
Shape	Rectangular
Outer Lens Material	Acrylic
Outer Lens Color	Clear
Housing Color	Black
Bezel Color	Black
Mounting Hardware Description	Single Carriage Bolt
Mating Connector	PE 12110293
Product Weight	1.47 lbs / 0.67 kgs
Shipping Weight	1.72 lbs / 0.78 kgs



Electrical Specifications

Input Voltage	12-72V DC
Operating Voltage	10-90V DC
Red Wire	+ Power
White Wire	- Ground
Black Wire	Mode Selection
Current Draw	3.6A @ 12V DC (Mode 0)

Photometric Specifications

Beam Pattern(s)	Warning - Keep Out Zone

Copyright © 2026 Invision Sales Pty. Ltd.

Additional Specifications

IP Rating	IP69K
Warranty	Please refer to the Warranty Statement which is available for download on the website
Certification	ECE Reg 10
Pack Quantity	1

Installation & Application Information

Black Wire is Mode Selection:
Select desired mode by touching black wire to Power + (1-2 sec)
Mode will switch to next state per table below.
Once desired state is set black wire can be removed or capped off.
Lamp will remain in selected mode.

Mode:
Mode Selection 0
Outter LED: Steady On, Inner LED: Steady On

Mode Selection 1
Outter LED: Flash 60 per min (1Hz), Inner LED: Flash 60 per min (1Hz)

Mode Selection 2
Outter LED: Triple flash 60 per min (1Hz), Inner LED: Triple flash 60 per min (1Hz)

Mode Selection 3
Outter LED: Flash 60 per min (1Hz), Inner LED: Triple flash 60 per min (1Hz)

Mode Selection 4
Outter LED: Flash 200 per min (2Hz), Inner LED: Flash 200 per min (2Hz)

Mode Selection 5
Outter LED: Flash 60 per min (1Hz), Inner LED: Steady On

Copyright © 2026 Invision Sales Pty. Ltd.