



Heated Lens LED Products

1403471

Product Information

Description Model 670 - 12/24V Heated

Worklamp - Flood Beam 162.31 mm / 6.39 in

 Height
 162.31 mm / 6.39 in

 Width
 123.95 mm / 4.88 in

 Depth
 52.58 mm / 2.07 in

Shape Round

Outer Lens Material Polycarbonate

Outer Lens Color Clear

Housing Material Polycarbonate

Housing Color Black

Mounting Hardware Description5/16-18 x 1" Mounting BoltMounting TypeUniversal Pedestal Mount

 $\begin{tabular}{ll} \begin{tabular}{ll} \be$

Connector or Wiring Integrated 2-Pin Deutsch Weather-

Proof Socket (DT04-2P)

Mating Connector2-Pin Deutsch Weather-Proof Plug

(DT06-2S)

Product Weight 1.41 lbs / 0.64 kgs **Shipping Weight** 1.41 lbs / 0.64 kgs



Electrical Specifications

Input Voltage12-24V DCOperating Voltage10-30V DCRed WirePositiveBlack WireNegative

Current Draw 1.3A @ 12V DC (Without Heat)

0.6A @ 24V DC (Without Heat) 2.1A @ 12V DC (With Heat) 1.1A @ 24V DC (With Heat)









Photometric Specifications

~

Raw Lumen Output1,080Effective Lumen Output780Nominal LED Color Temperature5000 K

Beam Pattern(s) Forward Lighting - Flood (Standard)

Additional Specifications

~

IP Rating IP69K

Warranty Please refer to the Warranty

Statement which is available for

download on the website

Certification SAEJ1113-13, Tested to ECE Reg.

10 (Radiated Emissions only)

Pack Quantity 1





