LED Compact Work Light – Model 792

1603931

Product Information

Description	Model 792 - 36/90V LED Work Light - Pedestal Mount
Height	76.10 mm / 3 in
Width	98.80 mm / 3.89 in
Depth	43.40 mm / 1.71 in
Shape	Rectangular
Outer Lens Material	Polycarbonate
Outer Lens Color	Clear
Housing Color	Black
Mounting Hardware Description	(x1) 5/16"-18 x 1.00" Mounting Bolt Bracket
Minimum Operating Temperature	-40 °C
Maximum Operating Temperature	65 °C
Mating Connector	JAE Connector MX19A003S51 harness included with flying leads
Product Weight	0.40 lbs / 0.18 kgs
Shipping Weight	7.19 lbs / 3.26 kgs



Electrical Specifications

Input Voltage	36-80V DC
Operating Voltage	30-95V DC
Transient Spike Protection	330V Peak @ 1 HZ-100 Pulses
Red Wire	Power
Black Wire	Ground
Current Draw	0.75A @ 36V DC (Power) 0.56A @ 48V DC (Power) 0.34A @ 80V DC (Power)

Copyright © 2026 Invision Sales Pty. Ltd.

Photometric Specifications

Raw Lumen Output	3630
Effective Lumen Output	2000
Candela Output	2900
Nominal LED Color Temperature	5050 K

Additional Specifications

IP Rating	IPIP67 & IP69K
Certification	Please refer to the Warranty Statement which is available for download on the website
Pack Quantity	1

Copyright © 2026 Invision Sales Pty. Ltd.