

# NX3 - LED Beacons


## NX351

### Product Information

<b>Description</b>	Amber LED Beacon - Low Profile - Magnetic Mount w/ 12V Vehicle Plug
<b>Height</b>	51 mm / 2.01 in
<b>Width</b>	110 mm / 4.33 in
<b>Depth</b>	110 mm / 4.33 in
<b>Shape</b>	Round
<b>Outer Lens Material</b>	Polycarbonate
<b>Housing Material</b>	Die-Cast Aluminum
<b>Housing Color</b>	Black
<b>Mounting Hardware Description</b>	Magnetic Mount
<b>Minimum Operating Temperature</b>	-40 °C
<b>Maximum Operating Temperature</b>	65 °C
<b>Connector or Wiring</b>	2.5m cable with 12V vehicle accessory plug
<b>Product Weight</b>	1.300066 lbs / 0.59 kgs



## Product Dimensions



## Electrical Specifications



<b>Input Voltage</b>	12-24V DC
<b>Operating Voltage</b>	12-24V DC
<b>Wattage</b>	24 W
<b>Current Draw</b>	3.1AA @ 13.8V DC 1.7AA @ 24V DC












Additional Specifications

IP Rating	IP67
Warranty	3 Years
Certification	EMI: CISPR 25 Class 3, ECE R10 - Operation: ECE R65 Class 1 & SAEJ845 Class 1
Pack Quantity	1 Beacon

Installation & Application Information

Flash Modes

*Note: This product does have mode memory*

-  Single Flash – 2.1Hz 126 Flash / Min – ECE R65 Class 1
-  Single Flash – 1.25Hz 75 Flash / Min
-  Double Flash
-  Triple Flash
-  Quadruple Flash
-  Quintuple Flash
-  Rotating
-  Combo – Single / Triple Flash
-  Combo – Single / Quintuple Flash
-  Strobe
-  Cruise / Solid On – 30% Brightness for night use