

NX3 - LED Beacons


NX362

Product Information

Description	Amber LED Beacon - Medium Profile - DIN Pole Mount
Height	148 mm / 5.83 in
Width	111 mm / 4.37 in
Depth	111 mm / 4.37 in
Shape	Round
Outer Lens Material	Polycarbonate
Housing Material	Die-Cast Aluminum
Housing Color	Black
Minimum Operating Temperature	-40 °C
Maximum Operating Temperature	65 °C
Connector or Wiring	DIN Pole Mount
Product Weight	1.1369239 lbs / 0.52 kgs



Product Dimensions



Electrical Specifications



Input Voltage	12-24V DC
Operating Voltage	12-24V DC
Wattage	16 W
Current Draw	1.7AA @ 13.8V DC 1.0AA @ 24V DC

Additional Specifications














IP Rating	IP67
Warranty	3 Years
Certification	EMI: CISPR 25 Class 3, ECE R10 - Operation: ECE R65 Class 1 & SAEJ845 Class 1
Pack Quantity	1 Beacon

Installation & Application Information



Flash Modes

Note: This product does have mode memory

-  Single Flash – 2.1Hz 126 Flash / Min – ECE R65 Class 1
-  Single Flash – 1.25Hz 75 Flash / Min
-  Double Flash
-  Triple Flash
-  Quadruple Flash
-  Quintuple Flash
-  Rotating
-  Combo – Single / Triple Flash
-  Combo – Single / Quintuple Flash
-  Strobe
-  Cruise / Solid On – 30% Brightness for night use