



×

LED Work Light – Model 4415 0551753

Product Information

Description

Right)
110.00 mm / 4.33 in
85.20 mm / 3.35 in
21.10 mm / 0.83 in
Round
Die-Cast Aluminum
Black
(x2) 0.500-13 x Bracket and Swiv
-40 °C
85 °C
Packard# 12084167
Packard# 12059183
1.00 lbs / 0.45 kgs
2.30 lbs / 1.04 kgs
Kit includes 2 lights and necessa mounting hardware.

- Spot Beam (Mirror Kit - Left & ivel sary

Model 4415 - 12/24V LED Worklight







Product Dimensions



Electrical Specifications

Input Voltage	12-24V AC
Operating Voltage	10-32V AC
Red Wire	Positive
Black Wire	Negative
Current Draw	2.2A @ 12V AC 1.1A @ 24V AC

Headlight INVISION. J.W. SPEAKER.) DCXSOLIS.



×

×



Photometric Specifications

Raw Lumen Output	2,450
Effective Lumen Output	1,350
Nominal LED Color Temperature	5000 K
Beam Pattern(s)	Forward Lighting - Spot



Additional Specifications

IP Rating	IP67
Warranty	Please refer to the Warranty Statement which is available for download on the website
Pack Quantity	2



 \sim

×



Installation & Application Information

This kit is intended to be mounted on the side mirrors or forward of the driver with the shroud (snoot) oriented to block the light from the driver / operator's eyes, providing maximum visibility rearward.

The kit can also be mounted elsewhere on the truck, such as on the back or side of a sleeper cab, to provide additional lighting.



INVISION. J.W. SPEAKER. DCXSOLIS.



 $\mathbf{\mathbf{v}}$