LED Headlight – Model 8632 Evolution


0551973

Product Information

Description	Model 8632 EVO - 12/24V LED Headlight - Pedestal Mount
Height	173.00 mm / 6.81 in
Width	144.00 mm / 5.67 in
Depth	86.00 mm / 3.39 in
Shape	Round
Outer Lens Material	Polycarbonate
Outer Lens Color	Clear
Housing Color	Black
Minimum Operating Temperature	-34 °C
Maximum Operating Temperature	49 °C
Connector or Wiring	Integral Connector in Housing simulating Delphi 12124107,
Mating Connector	Delphi 12052848
Product Weight	4.00 lbs / 1.81 kgs
Shipping Weight	5.40 lbs / 2.45 kgs



Product Dimensions




Copyright © 2026 Invision Sales Pty. Ltd.


Electrical Specifications

Input Voltage	12-24V AC
Operating Voltage	10-32V AC
White Wire	High Beam
Yellow Wire	Low Beam
Black Wire	Ground
Red Wire	Front Position
Purple Wire	DRL
Orange/white Wire	Front Turn
Current Draw	3.67A @ 12V AC (High Beam) .08A @ 12V AC (Side Marker) .042A @ 24V AC (Side Marker) 1.83A @ 24V AC (High Beam) 2.5A @ 12V AC (Low Beam) 1.25A @ 24V AC (Low Beam) .67A @ 12V AC (DRL) .34A @ 24V AC (DRL) .83A @ 12V AC (Front Turn) .42A @ 24V AC (Front Turn) .08A @ 12V AC (Front Position) .042A @ 24V AC (Front Position)

Photometric Specifications

Raw Lumen Output	2,925 (High Beam); 2,025 (Low Beam)
Effective Lumen Output	1,000 (High Beam); 630 (Low Beam)
Nominal LED Color Temperature	5000 K
Beam Pattern(s)	Forward Lighting - Daytime Running Light Forward Lighting - High Beam (DOT/ECE) Forward Lighting - Low Beam (ECE Left Hand) Signalization - Front Position Signalization - Marker Signalization - Turn (Front)





Copyright © 2026 Invision Sales Pty. Ltd.

Additional Specifications

IP Rating	IP67
Warranty	Please refer to the Warranty Statement which is available for download on the website
Certification	ECE Reg 6, 7, 87 & 112
Pack Quantity	2

Copyright © 2026 Invision Sales Pty. Ltd.